

WRE-Ringe

WRE-Rings



WRE-Sprengring für Kugellager phosphatiert

External retaining rings for ball bearings
Phosphate coated



Artikel-Nr.	Bezeichnung	Gewicht per 1.000	Welle d1	Ring d3/max.	Ring b/-0,2	Ring s/-0,1	Nut ds/h11	Nut d2/h11	Nut min.	Ablöse- drehzahl
Article-No.	Description	Weight per 1000	Wave d1	Rring d3/max	Rring b/-0,2	Rring b/-0,2	Nut ds/h11	Nut d2/h11	Nut min.	Transfer speed
66976	WRE 42	5,70	42	39,3	3,6	1,5	1,7	39,8	1,6	7680
66977	WRE 47	6,35	47	44,3	3,6	1,5	1,7	44,8	1,6	5840
66978	WRE 55	7,36	55	51,8	3,6	1,5	1,7	52,8	1,6	5660
66979	WRE 62	8,26	62	58,8	3,6	1,5	1,7	59,8	1,6	4220
66980	WRE 68	16,25	68	64,6	4,8	2,0	2,5	65,8	2,2	4710
67491	WRE 75	17,88	75	71,6	4,8	2,0	2,5	72,8	2,2	3720
66981	WRE 80	19,05	80	76,6	4,8	2,0	2,5	77,8	2,2	3180
66982	WRE 90	32,47	90	86,3	5,8	2,5	3,0	87,8	2,6	3140
66983	WRE 95	34,23	95	91,3	5,8	2,5	3,0	92,8	2,6	2760
66984	WRE 100	23,08	100	95,9	5,8	2,5	3,0	97,4	2,6	2460
66985	WRE 110	39,33	110	105,4	5,8	2,5	3,0	107,1	2,6	2090
66986	WRE 115	41,09	115	110,4	5,8	2,5	3,0	112,1	2,6	1880
66987	WRE 125	58,32	125	120,1	7,5	2,5	3,0	122,1	2,6	2080
66989	WRE 130	60,50	130	124,9	7,5	2,5	3,0	127,1	2,6	1990
66990	WRE 140	64,91	140	134,8	7,5	2,5	3,0	137,0	2,6	1660
66993	WRE 145	67,18	145	139,8	7,5	2,5	3,0	142,0	2,6	1530
66994	WRE 150	69,28	150	144,4	7,5	2,5	3,0	147,0	2,6	1530
66996	WRE 160	73,70	160	154,1	7,5	2,5	3,0	157,0	2,6	1380
66997	WRE 170	77,92	170	163,4	7,5	2,5	3,0	167,0	2,6	1330
66998	WRE 180	131,09	180	173,0	9,8	3,0	3,5	176,0	3,2	1350
67000	WRE 190	138,23	190	183,0	9,8	3,0	3,5	186,0	3,2	1190

WRE-Sprengring für Kugellager phosphatiert

External retaining rings for ball bearings
Phosphate coated



Artikel-Nr.	Bezeichnung	Gewicht per 1.000	Welle d1	Ring d3/max.	Ring b/-0,2	Ring s/-0,1	Nut ds/h11	Nut d2/h11	Nut min.	Ablöse- drehzahl
Article-No.	Description	Weight per 1000	Wave d1	Rring d3/max.	Rring b/-0,2	Rring b/-0,2	Nut ds/h11	Nut d2/h11	Nut min.	Transfer speed
67013	WRE 230	205,24	230	222,0	12,0	3,0	3,5	226,0	3,2	1030
67015	WRE 240	213,54	240	231,5	12,0	3,0	3,5	236,0	3,2	990
67018	WRE 260	359,35	260	249,5	14,0	4,0	4,0	254,0	4,2	950
67020	WRE 270	372,25	270	259,0	14,0	4,0	4,0	264,0	4,2	910
67022	WRE 280	385,84	280	269,0	14,0	4,0	4,0	275,0	4,2	840
67024	WRE 290	399,43	290	279,0	14,0	4,0	4,0	284,0	4,2	770
67026	WRE 300	412,33	300	288,5	14,0	4,0	4,0	294,0	4,2	740
67028	WRE 210	495,52	310	298,0	16,2	4,0	4,0	304,0	4,2	810
67030	WRE 320	511,24	320	308,0	16,2	4,0	4,0	314,0	4,2	750
67031	WRE 340	541,89	340	327,5	16,2	4,0	4,0	334,0	4,2	680
67033	WRE 360	572,55	360	347,0	16,2	4,0	4,0	354,0	4,2	610
67035	WRE 380	600,85	380	365,0	16,2	4,0	4,0	374,0	4,2	610
67036	WRE 400	650,00	400	385,0	16,2	4,0	4,0	394,0	4,2	540
67037	WRE 420	930,00	420	405,0	20,0	4,0	4,0	413,0	4,7	540
67038	WRE 460	1011,00	460	442,0	20,0	4,5	4,0	453,0	4,7	510